ThinkPad T490 Platform Specifications

Processor	8th G	enerati	on Inte	I® Core [⊤]	[™] i5 / i7 Pr	ocessor					Dimensions	WxDxH:			m x 227mm x 17.9mm	
	Proce			# of		Max Turbo Cache		Memory	Processor Graphics		Weight	Models	HD	FHD	FHD Low Power / WQHD	-
	Number Cores		ores Tr			requericy		Types				Weight	3.37 lb / 1.53 kg	3.41 lb / 1.55 kg	3.23 lb / 1.46 kg	3.56 lb / 1.61 kg
	i5-8265U						SMB				Case color Case material	Black Display cover: BBS / E09/ CE:				
	i5-836		4	× –			SMB SMB	DR4-2400	Intel UHD Graphi 620		Case material	Display cover: PPS / 50% GF; Bottom: PA / 50% GF				
	i7-866			_			BMB		020	,	Smart card reads			-		
			ration					ailahla in F	:MEA)		Smart card reader <i>Optional:</i> Smart card reader Media reader MicroSD card reader					
	or 10th Generation Intel Core i5 / i7 Processor (NOT available in EMEA) Processor # of # of Base Max Turbo Memory Processor									ccor	Ports	Two USB 3.1 Gen 1 (one Always On),				
				Threads F	requency	Frequency C	ache	Types	Grap			one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort) one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP), HDMI 1.4b, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, microSD card reader, side docking connector, security keyhole * Depending on many factors, actual data transfer speed may be lower than theoretical spee				
	i7-10		4	8			MB F		Intel UHD Graphics							
	i7-10		6		1.1 GHz		12MB									
				-												
						Graphics in			or		Monitor cable (optional)	HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter				
	Intel UHD Graphics 620 or Intel UHD Graphics in processor and NVIDIA® GeForce® MX250, 2GB GDDR5 memory;										(op normal)	USB-C to VGA. Lenovo USB-C to VGA Adapter				
	supports external digital monitor via HDMI or Thunderbolt;										D "	USB-C to		USB-C to Displa		
	supports three independent displays; Max resolution: 4096x2304@60Hz (Thunderbolt); 4096x2160@24Hz (HDMI)									N #1\	Bundled Accy	None				
						nunaerboit)	; 409	6X216U@2	4HZ (HD	VII)	Camera (optional	I) One of the	following, configu	rable by model:		
Chipset Memory	Intel SoC (System on Chip) platform 40GB or 48GB max / 2400MHz DDR4, dual-channel capable,											• HD/20	o camera with I	hinkShutter came	era privacy, fixed focus	cy fixed focus
	8GB or 16GB memory soldered to systemboard, one DDR4 SO-DIMM socket										Audio support	• IR camera and HD720p camera with ThinkShutter camera privacy, fixed focus HD Audio, Realtek® ALC3287 codec /				
	* Installed memory is actually 2666MHz but run at 2400MHz due to Intel limitation											stereo sp	eakers, 2W x 2,	Dolby® Audio™ F	Premium /	
Display Multi-touch (opt)	Size Resolution				Res Surface Brightness Aspect Contrast Color Viewing					Viewing	ā	dual array far-field microphone (optional for special bid model), headphone / microphone combo jack				
				Тур		Brightness	Ratio	Ratio	Gamut	Angle			•		antianal I ED haaldinkt	
	14.0"	HD (136	6x768)	TN	Anti-glare	+	16:9	400:1	45%	90°	Keyboard UltraNav™	b-row, sp TrackPoir	III-resistant, mui nt®nointing devic	timedia Fri Keys, ce and huttonless	optional LED backlight Mylar surface multi-tou	ch touchnad
						250 nits (non-touch)					Security				supervisor password, se	-
	14.0"	FHD (19	20x108	0) IPS	Anti-glare	300 nits	16:9	700:1	45%	170°	Security chip				r discrete TPM 2.0 TCG	
						(multi-touch)						(may be	disabled in some			
	14.0"	FHD (19 Low Pov		⁽⁰⁾ IPS	Anti-glare	400 nits	16:9	800:1	72%	170°	System Mgt (opt)	Intel vPro	Technology			
		FHD (19		080)	+			 	+		NFC (optional)	er <i>Optional:</i> Near Fiel	d Communication	aten on enip finge on	rprint reader on the paln	n rest
	14.0"	ThinkPa	d Privac	y IPS	Anti-glare	400 nits	16:9	1000:1	72%	170°	Battery				Rapid Charge (charge up	to 90% in 1hr
		Guard					-				Dallery		AC adapter	attery, supports r	hapiu Charge (charge up) to 60 % iii 11ii)
	14.0"	WQHD HDR, D	2560x1	440) IPS	Glossy	500 nits	16:9	1500:1	100% Adobe	170°	Max battery life	MobileMa	a <i>rk® 2014:</i> 16.1			
					finant ann	sture (FHD only)			raobe	1	AC adapter	* Battery life varies significantly with settings, usage, & other factors • 45W USB-C AC adapter				
							-,	- A \			AC adapter		65W USB-C AC adapter			
-					Me, PCle	T available i	n EIVIE	=A)				 65W sl 	im tip AC adapte	er		
					Me, PCle						Operating system	n • Window	rs® 10 Home 64			
	 Intel Optane™ Memory H10 with Solid State Storage, 										(optional)		rs 10 Pro 64			
Optical	M.2 2280, PCle NVMé 3.0 x 4												s 10 Pro in S m			
	None										Limited warranty		lepot repair serv		anair aaruiga	
Ethernet	Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville)										(optional)	 1-year depot with 2-year system board repair service 1-year limited onsite service 3-year/1-yr battery depot repair service 				
WLAN +	One of the following, configurable by model:										1					
Bluetooth™	Intel Wireless-AC 9560, Wi-Fi 2x2 802.11ac + Bluetooth 5.0											 1-year + 2-year depot repair service 3-year/1-yr battery depot repair service 				
(optional)	Inte	Intel Wi-Fi 6 AX201, Wi-Fi 2x2 802.11ax + Bluetooth 5.0										 3-year/1 	1-yr battery depo	ot repair service ed onsite service		
	(AX201 for 10th Gen processor only)										Mil-Spec test		-810G military to			
WWAN (optional)											I				IC compliant	
						bid only in E E, Fibocom		ER M200	rd (EME	A only)	Environment	EPEAI™	Gold; ENERGY	' STAR® 7.1; RoH	io-compliant	
	• Inte	grated	Mobile	Broadh	and 4G LT	E-A. Fiboco	m L85	50-GL. M.2	card	- Orny)						
	 Integrated Mobile Broadband 4G LTE-A, Fibocom L850-GL, M.2 card Integrated Mobile Broadband 4G LTE-A, Fibocom L860-GL, MIMO 4x4, M.2 card 															
0114	* For non-WWAN model, it means the model is NOT WWAN upgradable Nano-SIM card slot, optional Verizon LTE (US) SIM card															
SIM card (opt)		- III /I O	ıra sınt	Ontions	ai verizon	$\Box \vdash (\Box S) S$	IVI car	0			1					